
HP Natural Tracing Paper





The HP DesignJet printing system—the complete solution

HP DesignJet printers, Original HP inks and printheads, Original HP printing materials and HP Scitex printers, are designed to work together as a system to provide reliable, consistent results with every print.



Produce clear reproducible final drawings

Communicate with clarity

Clear, concise drawings can avoid costly mistakes. Achieve crisp black and color line quality—HP Natural Tracing Paper provides excellent bleed control—for archivable prints.

Deliver easy-to-read plans

Your technical drawings need to communicate without ambiguity. Produce easy-to-understand, easy-to-read reproducible prints with HP Natural Tracing Paper, designed together with Original HP inks.

Deliver on time, on budget

Get the results you expect with the first print. HP printing materials are designed together with Original HP inks and your Designjet printer to provide consistent, quality results.

| Target customers | Applications | Benefits |
|--------------------------------------|---|------------------------------------|
| Architects | Engineering (CAD), architecture (AEC), and Geographic Information Systems (GIS) archives or reproductions | Crisp black and color line quality |
| Engineers | | Excellent bleed control |
| Geographic Information Systems (GIS) | | Archivable prints |

Technical specifications



HP Natural Tracing Paper

For the latest ICC/media profiles and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit **HPLFMedia.com**.

| Weight | 90 g/m² per ISO 536 Test Method | | | | | |
|-----------------------|--|---|-------------------------------|--|--|--|
| Thickness | 76 microns/3 mil per ISO 534 Test Method | | | | | |
| Opacity | 25% per TAPPI T-425 Test Method | | | | | |
| Brightness | 61% per TAPPI T-452 Test Method | | | | | |
| Finish | Matte | | | | | |
| Operating temperature | 15 to 35° C / 59 to 95° F | | | | | |
| Operating humidity | 20 to 80% RH | | | | | |
| Dry time | Less than 2 minutes (at 23°C, 50% RH) | | | | | |
| Shelflife | 1 year, unopened in original packaging | | | | | |
| Storage temperature | 0 to 40° C / 32 to 104° F | | | | | |
| Storage humidity | 5 to 95% RH | | | | | |
| Country of origin | Product of United Kingdom | | | | | |
| Ordering information | Product numbers C3869A | Roll sizes 610 mm x 45,7 m (24 in x 150 ft) | UPC Codes 848412014211 | Region North America, Europe, Asia | | |
| | C3868A | 914 mm x 45,7 m (36 in x 150 ft) | 848412014228 | Americas, Europe, Asia | | |
| | Q1439A | (A1) 594 mm x 45,7 m (23.4 in x 150 ft) | 848412014204 | Japan | | |
| | | | | | | |
| Warranty | HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see <u>HPLFMedia.com/mediawarranties</u> . | | | | | |





For detailed information on the HP large format printing materials portfolio and to order, see HPLFMedia.com

