




HP PVC-free Wall Paper



The HP large format printing system—the complete solution

HP Designjet and HP Scitex printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



Differentiate with PVC-free¹ wall murals

Differentiate with environmental certifications

Offer bold wall decorations and more—provide reassurance with environmental certifications and responsible sourcing. Odorless displays are GREENGUARD Children & Schools Certified^{SM2} and meet AgBB criteria³ using this FSC®-certified paper.

Be productive—easy to print, install, and remove

Maintain high productivity in your printshop and offer your customers an easy-to-use solution. This wall paper goes up—and comes down—with water, and it comes with an HP warranty.⁴

Help your customers boldly define interior spaces

Help your customers define interiors with long-lasting, colorful, detailed, creative wall murals. Expand your offering with HP PVC-free Wall Paper, 175 g/m²—the competitive digital solution from HP designed for emerging wall mural applications.

Target customers	Applications	Benefits
Print service providers	Wall murals	PVC-free ¹ alternative, easier to dispose of than most PVC-based substrates
	Creative design applications	Mold and mildew resistant ⁵
		Vivid color, high-definition detail
		Ultra-smooth finish
		20+ years indoor display permanence ⁶
		Prepaste facilitates easy application
		Strippable and easy to remove, with an HP warranty ⁴
		Flame resistant ⁷
		Carries the CE mark ⁸

Technical specifications



Eco Highlights

- FSC®-certified paper from well-managed forests
- Paper contains 10% recycled content from post-consumer waste
- When printed with HP Latex Inks, the prints produced:
 - Are odorless
 - Are GREENGUARD Children & Schools Certified^{SM1}
 - Meet AgBB criteria for health-related evaluation of VOC emissions of indoor building products²



HP PVC-free Wall Paper

Weight	175 g/m² per ISO 536 Test Method		
Thickness	177 microns/7 mil per ISO 534 Test Method		
Opacity	94% per TAPPI T-425 Test Method		
Brightness	83% per ISO 2470 Test Method		
Whiteness	85 per ISO 11475 Test Method		
Finish	Matte		
Operating temperature	15 to 30° C / 59 to 86° F		
Operating humidity	15 to 80% RH		
Display permanence (Indoor home or office)	20+ years, away from direct sun with HP Latex Inks ⁹		
Display permanence (Commercial in-window)	3+ years, unlaminated with HP Latex Inks ¹⁰		
Water resistance	Water resistant with HP Latex Inks ¹¹		
Flame resistance	Class A, B1, EN 13501, and M1 approved fire certifications		
Shelf life	1 year, unopened in original packaging		
Storage temperature	15 to 30° C / 59 to 86° F		
Storage humidity	15 to 80% RH		
Country of origin	Product of United States		
Ordering information	Product numbers	Roll sizes	UPC codes
	CH098B	1067 mm x 30,5 m (42 in x 100 ft)	848412009699
	CH003B	1372 mm x 30,5 m (54 in x 100 ft)	848412009675
	CH103A	1372 mm x 91,4 m (54 in x 300 ft)	848412009682
Region			
North America, Europe, Asia			
North America, Europe, Asia			
North America, Europe, Asia			
Warranty	HP offers a range of self-adhesive materials with warranties that guarantee these products to be free of material or coating flaws and defects that affect the final use of the print and meet HP published specifications. These warranties also cover key performance characteristics such as display permanence and easy removal from specified surfaces. ¹²		



The mark of responsible forestry
Note: Not all FSC®-certified product is available in all regions.

