

Redefining the Large-Format Printer.

Up to 144 D Prints/Hour

LUCIA TD Pigment Ink Scan-to-Copy/File/ Share Solution Available



Print Head

PF-06

Number of Nozzles

Matte Black: 5,120 Nozzles

Other Colors: 2,560 Nozzles per Color

Droplet Size

5 Picoliter

Ink Type

Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)

Shipped with Printer: MBK (130 ml), BK, C, M, Y (90 ml) Replacement: PFI-120 (130 ml) or PFI-320 (300 ml)

128 GB (2 GB Physical Memory)

Media Feed

Roll Feed: One Roll, Top-loading, Front Output

Roll Feed: 8"-36" (203 mm - 914 mm) Cut Sheet: 8"-36" (203 mm - 914 mm)

Durable Dual-Blade Rotary Cutter

Media Thickness

 $0.07 - 0.8 \, mm$

Media Core Sizes

2" and 3" Core (Adapters Included)

Maximum Roll Outer Diameter

5.9" (150 mm)

Media Output

Flat Stacking Basket (Standard)

Printing Software Utilities

Accounting Manager, Canon Print Service, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac® Media Configuration Tool, PosterArtist Lite for Windows, Canon PRINT Inkjet Selphy, Easy-Photo PrintEditor, Optimized Driver for AutoCAD®

Operating System

Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows Server 2008 R2, (32/64-bit), Windows Server 2012 (64-bit), Windows Server 2012 R2 (64-bit), Windows Server 2016 (64-bit), Macintosh OS X v10.10.5-v10.12x

Printer: SGRaster, HP-GL/2, HP RTL, JPEG

Standard (Built-in): USB 2.0 Hi-Speed, 10/100/ 1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)*, Direct USB Thumb Drive

Power Supply

AC 100 - 240V (50 - 60 Hz)

Power Consumption

Maximum: 69 W or Less Standby: 3.6 W or Less

Power Off: 0.3 W or Less (Executive Order Compliant)

Certifications

Environmental Certifications ENERGY STAR® (Worldwide)

Operational Environment

Temperature: 59° – 86° F (15° – 30° C)

Relative Humidity: 10 - 80% (Non Condensation)

Printer Dimensions (H x W x D) and Weight

(With Basket Opened)

42" x 51" x 35" Approx. 134 lb.

Package Dimensions (H x W x D) and Weight

(With Stand, Basket, and Pallet)

38" x 58" x 36" Approx. 231 lb.

- 2"/3" Roll Holder Set (RH2-35)
- PosterArtist

User-Replaceable Items

- Ink Tank (PFI-120/PFI-320)Print Head (PF-06)
- Maintenance Cartridge (MC-31)
- Cutter Blade (CT-08)

What's In The Box

Printer, Basket, Stand, 2"/3" Core Media Spool (Adapters Included), Power Cord, Tools and Screws, Print Head, Maintenance Cartridge (Installed), 5 Ink Tanks (130 ml: MBK, 90 ml: BK/C/M/Y), Sample Heavyweight Coated Paper (A2/2 Sheets), Ethernet Card (built-in), USB 2.0 High-speed Interface, USB Connection Sheet, iWR Service Terms Leaflet, User Manual, Quick Setup Guide, User Software CD for Windows (Printer Driver Utilities), PosterArtist Lite CD, User Registration Card

Z36 SCANNER

Scan Speed

- 24-bit Color @ 200 dpi: 3" (Per Second)
- 8-bit Grayscale and Monochrome @ 200 dpi 13" (Per Second)

Scan Modes

- 16.7 Million Color RGB (24-bit)
- 256-level Grayscale (8-bit)
- Black and White (1-bit)

Color Space

sRGB

Maximum Resolution

1200 dpi (Optical)

Scan Accuracy

+/- 0.1%: +/- 1 pixel

Maximum Scan Width

Maximum Media Width

Maximum Scan Length

315" (JPEG/PDF); 598" (TIFF)

Maximum Media Thickness

0.003" - 0.04" (0.07 mm - 1.0 mm)

Digital Imaging Technology

Contact Image Sensor (CIS) Technology (SingleSensor Assembly)

- 24-bit RGB digital color image capture
- 16-bit grayscale image capture
- Panchromatic monochrome and black and white
- · Bi-directional extra long-life LED light system for optimum object illumination and instant-on scanning capability

Included Software

SmartWorks MFP Scan-to-Copy/File/Email with Real-time Image Viewer; supports TIFF, JPEG, TIFF G4, and PDF

Operating System

Windows 10 LTSC

Scanner Interface Kit

Superspeed USB 3.0 (PC Connector Compatible with USB 2.0 and USB 3.0 sockets)

Operating Environment

10° C - 35° C, 35 - 80% RH, Non-condensing

External Power Supply

100 - 240 VAC Autosensing +/- 10%, 50 - 60 Hz

Scanner Power Consumption

Sleep/Idle: 0.2 W/12.4 W

Scanning Color/Grayscale @ 200 dpi: 22.7 W/23.3 W

Compliance

ENERGY STAR®, CB (62368-1), CE, FCC (EMC), Cul/UL, CCC, NOM-019, EAC, C-TICK, VCCI, BIS, EMC +LOÁ, UL AR, WEEE, REACH, RoHS, EU-Tier 3 of Lot 6

Scanner Dimensions (H x W x D) 7" x 42" x 10"

Scanner Weight

17.3 lb. (Approx.)

What's In The Box? • Z36 Scanner with Power Cord, USB 3.0 Cable (2 meter)

- 15.6" System Controller
- 3:1 Trident Power Cord
- Power Supply
 Mount for Printer and System Controller
- 2 Paper Edge Guides
- Document Return Guides
- Calibration Target
 Assembly and Startup Guide
- Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.
- The scan rate is proportional across the full range of resolutions supported by the scanner. Actual scan times will depend on the host system performance. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types.
- The quoted scan accuracy may vary depending on the operating environment and the thickness of the media

Note: The imagePROGRAF TM Series MFP Z36 systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability with respect to such third-party offerings.





0621-TM305MFPZ36SS-PDF-IH













