

### **Technical Specifications**

# Matte Canvas High White 350gsm

## Fine Art Range IFA 35

**Product Description** Polycotton Canvas with flexible Matte coating.

#### Features

- High White
- Archival Acid and Lignin Free
- Instant Dry
- Aqueous Pigment and Dye Ink Compatible
- Excellent Colour Gamut
- Exceptional D-max
- · Compatible with Water based and Solvent giclée varnishes
- Ideal for stretching

#### Applications

- Fine Art and Photographic Open and Limited Edition Prints
- Stretched Canvases and Gallery Wraps
- Compatible with JetMaster Photo Wrap framing system

Basic Weight (gsm)	350		
Canvas Thickness (Microns)	405	Canvas Thickness (Inches)	0.016
Base Material	Polycotton		
Coating Type	Matte		
Surface Texture	Canvas		
Whiteness (CIE)	152		
Brightness (TAPPI)	88		
OBA Content	Yes		
рН	7.5-9.5		
Recyclable	Yes		
Print Settings*	MK Ink, an Art Matte Canvas Setting is recommended as a starting point		
Notes			

\*Generic ICC Profiles for selected printer models are available from the Innova Art website.

Sheets	A4, A3
Rolls (15m Length)	60", 44", 36", 24", 17"

Additional Sizes are available on request, subject to order quantity.

#### Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

#### **Conditions of Use**

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.

